



SIZES

Eco-Duo Continuous Isolation Valve for 15mm	W1599 RD	0.30kg
Eco-Duo Continuous Isolation Valve for 22mm	W1600 RD	0.40kg
Eco-Duo Continuous Isolation Valve for 28mm	W1601 RD	0.70kg
Eco-Duo Continuous Isolation Valve for 35mm	W1602 RD	0.90kg
Eco-Duo Continuous Isolation Valve for 42mm	W1603 RD	1.10kg
Eco-Duo Continuous Isolation Valve for 54mm	W1604 RD	1.80kg

MATERIALS

Main Body: Brass
 Pipes: Copper
 Separators: 316 Stainless Steel

MAX PRESSURE

16 Bar up to 30°C

FEATURES AND BENEFITS

- Patented Pipe-in-a-pipe technology
- Saves 50% energy costs (tested by BRE)
- Maintains temperatures across the whole building.
- Halves installation time and costs
- 50% reduction in pipe fixings and insulation
- No special installation required
- Pipework can be cut as normal
- Helps to reduce the risk of Legionella and other water borne pathogens
- Can be used on hot and cold potable water systems

NOTES

- Only for use with potable water
- Only for use with pumped recirculated water

FINISHING OPTIONS

Copper CP

SKU	DESC	A	B	C	D
W1599 RD	15mm	78	46	90	15
W1600 RD	22mm	85	54	95	22
W1601 RD	28mm	100	57	110	28
W1602 RD	35mm	120	62	110	35
W1603 RD	42mm	135	77	140	42
W1604 RD	54mm	160	84	140	54

Water Kinetics Eco-Duo Guarantee - Terms and Conditions

Products are subject to a guarantee that is between Water Kinetics, registered at Lomond House 7 Greenbank Road, Darvel, East Ayrshire, United Kingdom, KA17 0NN, Company No: SC632550, VAT: GB 350 116 837, and the final purchaser of the product.

When correctly assembled with the stated tubes and pipe the length of guarantee is as follows:

25 Years

The Eco-Duo Copper and Stainless ranges are guaranteed for a period of 25 years commencing on the date of purchase when installed in conjunction with Eco-Duo fittings and components.

The guarantee is subject to proof of purchase being supplied.

This guarantee does not affect any statutory rights the purchaser may have in law.

The guarantee covers manufacturing or material defects when installed in accordance with our instructions on specified tube materials and applications and does not cover instances of normal wear and tear).

This product range has been designed for the use of domestic and commercial applications and therefore the guarantee is subject to the product being properly selected for their intended service conditions.

The guarantee is not applicable where the product is fitted contrary to the conditions contained within the fitting instructions.

Provided Eco-Duo is installed correctly and receives adequate preventative maintenance it should give years of trouble-free service.

Abusive behaviour, and accidental damage to the product are not covered by this guarantee.

The extent of any liability from this guarantee is limited to the cost of the replacement of the defective item and not to installation or consequential damages.

Eco-Duo is a trademark of Water Kinetics Ltd

Water Kinetics Ltd makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.