### **Coupling Street Reducer**

# **ECO**DU©




#### SIZES

Eco-Duo Coupling Street Reducer for 28mm x 22mm \* Eco-Duo Coupling Street Reducer for 35mm x 22mm \* Eco-Duo Coupling Street Reducer for 35mm x 28mm \* Eco-Duo Coupling Street Reducer for 42mm x 22mm \* Eco-Duo Coupling Street Reducer for 42mm x 28mm \* Eco-Duo Coupling Street Reducer for 42mm x 35mm \* Eco-Duo Coupling Street Reducer for 54mm x 35mm Eco-Duo Coupling Street Reducer for 54mm x 42mm Eco-Duo Coupling Street Reducer for 66.7mm x 28mm Eco-Duo Coupling Street Reducer for 66.7mm x 35mm Eco-Duo Coupling Street Reducer for 66.7mm x 42mm Eco-Duo Coupling Street Reducer for 66.7mm x 54mm Eco-Duo Coupling Street Reducer for 76.1mm x 35mm Eco-Duo Coupling Street Reducer for 76.1mm x 42mm Eco-Duo Coupling Street Reducer for 76.1mm x 54mm Eco-Duo Coupling Street Reducer for 76.1mm x 66.7mm Eco-Duo Coupling Street Reducer for 108mm x 42mm Eco-Duo Coupling Street Reducer for 108mm x 54mm Eco-Duo Coupling Street Reducer for 108mm x 66.7mm Eco-Duo Coupling Street Reducer for 108mm x 76.1mm \* Only available in packs of 10

#### FEATURES AND BENEFITS

Patented Pipe-in-a-pipe technology Saves 50% energy costs (tested by BRE) Maintains temperatures across the whole building. Halves installation time and costs 50% reduction in pipe fixings and insulation No special installation required Pipework can be cut as normal Helps to reduce the risk of Legionella and other water borne pathogens Can be used on hot and cold potable water systems



#### MATERIALS

Body: Copper Separators: 316 Stainless Steel

MAX PRESSURE

16 Bar

0.05kg

0.07kg

0.09kg

0.11kg

0.12kg

0.12kg

0.16kg

0.19kg

0.97kg

0.97kg

0.97kg

1.99kg

1.07kg

1.07kg

1.08kg

1.16kg

0.93kg

0.94kg

1.05kg

1.10kg

W8344 CP

W8345 CP

W8346 CP

W8347 CP

W8348 CP

W8349 CP

W1557 CP

W1558 CP

W1559 CP

W1560 CP

W1561 CP

W1562 CP

W1563 CP

W1564 CP

W1565 CP

W1566 CP

W8386 CP

W8387 CP

W8389 CP

W8390 CP

#### NOTES

Only for use with potable water Only for use with pumped recirculated water

#### FINISHING OPTIONS

Copper CP

### Coupling Street Reducer

SKU	DESC	l1	D1	d2	z1
W1551 CP	28-15mm	57	28	15	39
W1552 CP	35-22mm	68	35	22	44
W1553 CP	35-28mm	67	35	28	40
W1554 CP	42-22mm	77	42	22	54
W1555 CP	42-28mm	78	42	28	51
W1556 CP	42-35mm	90	42	35	46
W1557 CP	54-35mm	91	54	35	58
W1558 CP	54-42mm	91	54	42	53
W1559 CP	66.7-28mm	125	66.7	28	98
W1560 CP	66.7-35mm	126	66.7	35	94
W1561 CP	66.7-42mm	129	66.7	42	91
W1562 CP	66.7-54mm	128	66.7	54	85
W1563 CP	76.1-35mm	131	76.1	35	99
W1564 CP	76.1-42mm	134	76.1	42	96
W1565 CP	76.1-54mm	133	76.1	54	90
W1566 CP	76.1-66.7mm	130	76.1	66.7	81
W8386 CP	108-42mm	180	108	42	142
W8387 CP	108-54mm	179	108	54	136
W8389 CP	108-66.7mm	178	108	66.7	129
W8390 CP	108-76.1mm	174	108	76.1	124

#### Water Kinetics Eco-Duo Guarantee - Terms and Conditions

Products are subject to a guarantee that is between Water Kinetics, registered at Lomond House 7 Greenbank Road, Darvel, East Ayrshire, United Kingdom, KA17 ONN, Company No: SC632550, VAT: GB 350 116 837, and the final purchaser of the product.

When correctly assembled with the stated tubes and pipe the length of guarantee is as follows: **25 Years** 

The Eco-Duo Copper and Stainless ranges are guaranteed for a period of 25 years commencing on the date of purchase when installed in conjunction with Eco-Duo fittings and components.

The guarantee is subject to proof of purchase being supplied. This guarantee does not affect any statutory rights the purchaser may have in law.

The guarantee covers manufacturing or material defects when installed in accordance with our instructions on specified tube materials and applications and does not cover instances of normal wear and tear).

This product range has been designed for the use of domestic and commercial applications and therefore the guarantee is subject to the product being properly selected for their intended service conditions.

ECODUO

## Coupling Street Reducer

## **ECO**DU©

The guarantee is not applicable where the product is fitted contrary to the condit ions contained within the fitting instructions.

Provided Eco-Duo is installed correctly and receives adequate preventative maintenance it should give years of trouble-free service.

Abusive behaviour, and accidental damage to the product are not covered by this guarantee. The extent of any liability from this guarantee is limited to the cost of the replacement of the defective item and not to installation or consequential damages.

#### Eco-Duo is a trademark of Water Kinetics Ltd

Water Kinetics Ltd makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.